

[illegible]

	Pin	Spalva	Aprašymas
Žiūrėkite motorinės	-	žalia	Perjungimo impulsas (+)
spynos gamintojo	-	ruda	GND (-)
konfigūraciją/instrukciją	-	balta	VDC (+)

	Pin	Spalva	Aprašymas
	4	-	-
	3	žalia	Perjungimo impulsas (+)
	2	ruda	GND (-)
	1	balta	VDC (+)

Spalva	Aprašymas
balta	VDC (+) (12-24)
ruda	GND (-)
žalia	ekey duomenų magistralė
geltona	ekey duomenų magistralė
mėlyna	Įvestis
pilka	Įvestis
rožinė	Bandymų tikslais
raudona	Bandymų tikslais



Risk of electrocution: All key devices are to be operated with Safety Extra Low Voltage (SELV). Only use power supplies rated protection class 2 with safety approval according to EN 62368-1.

Failure to do so will create a risk of fatal electrocution.

Only certified electricians are authorized to carry out electrical installation work on mains systems.

Property damage in the event of incorrect mounting and wiring: The system devices are operated using electricity. They could be destroyed if they are mounted and wired incorrectly. Mount and wire the system devices correctly before connecting the power.

This wiring diagram is not subject to updating. We reserve the right to make technical modifications and change the product's appearance; any liability for errors and misprints is excluded.

- 1** ekey dLine skaitytuvas
450 007
- 2** ekey dLine FP laidas
- 3** ekey dLine valdiklis
450 008
- 4** ekey dLine MT laidas
- 5** ekey dLine kabelio
šarvas
201 401